

cowie[®] PTFE Bottles

[HOME](#)
[LABWARE INDEX](#)

- ✓ Isostatically molded in pure, FDA approved, PTFE
- ✓ Heavy wall construction with super smooth internal finish
- ✓ Screw cap housing for leak-free performance
- ✓ Suitable for low temperature applications
- ✓ Hand grips for ease of manipulation
- ✓ Use up to 280°C (540°F)

Totally chemically resistant and inert



PTFE Bottles

Reference	Volume ml (Fl oz)	Height (mm)	Dia. - Base (mm)	Dia. - Neck (mm)
015.001.2	1 (0.03)	27		
015.003.2	3 (0.10)	34	16	10
015.005.2	5 (0.17)	35	20	10
015.010.2	10 (0.30)	50	22	10
015.025.2	25 (0.83)	61	26	12
015.050.2	50 (1.67)	76	33	19
015.100.2	100 (3.33)	88	43	25
015.150.2	150 (5.00)	90	52	35
015.250.2	250 (8.33)	115	60	35
015.500.2	500 (16.7)	150	67	42
015.1000.2	1000 (33.3)	185	80	52
015.2000.2	2000 (66.6)	240	100	57
			120	60

NB: Do NOT USE when sealed for chemical reactions or digestions.
Loosen lid when thermally sterilising.